








RoHS  
Compliant

ZONE	EC N. NO.	DESCRIPTION	DRAWING	DATE
A		INITIAL	林生财	2020.02.18
Rating	DC30V 100mA	Electrical Life	20,000 cycles	
Contact Resistance	100mΩ Max	Mechanical Life	20,000 cycles	
Insulation Resistance	>100MΩ DC500V	Ambient Temper. Used	-25°C to +85°C	
Withstand Voltage	AC250V 1min.	Ambient Humidity Used	≤85% at +40°C	
Soldering Temper.	235±5°C 5s	Operating Force	50gf max	



7	压柄 (LEVER)	1	尼龙 (Nylon)	
6	端子 (TERMINAL)	3	C2680 (Brass)	镀银 (Silver plating)
5	触点 (CONTACT)	1	银合金 (Silver Alloy)	
4	按钮 (BUTTON)	1	PBT	
3	弹片 (SPRING)	1	C17200 (Beryllium copper)	
2	盖片 (COVER)	1	尼龙 (Nylon)	
1	底座 (BASE)	1	尼龙 (Nylon)	黑色 (Black)
序号 NO.	零件名称 Part Name	数量 Quantity	材质 Material	备注 Notes

**LZG** LZG INDUSTRIAL CO. LTD

PART NAME	超小型微动开关 (2.7井深)	TOLERANCE UNLESS	10<L<20 ±0.20	0.°±2°	UNIT:	APPROVAL:	DATE:	SCALE	1:1
PART NO.	DS027-01CR-30-3	OTHERWISE SPECIFIED:	6<L<10 ±0.15	0.0°±1°	mm				

DRAWING:	林生财	DATE:	2020.02.18	SCALE	1:1
CHECK:	李宏鑫	DATE:	2020.02.18	MATERIAL	*
DRAWING NO.	DS027-01CR-30-3		DATE:	2020.02.18	DWG. NO.
				SHEET	1/1